



## HARR LAW OFFICE, P.C.

Registered Patent Attorney  
1402 25<sup>th</sup> Street South  
Suite B  
Fargo, North Dakota 58103

Telephone (701) 298-3001  
Facsimile (701) 298-3002

### FACSIMILE TRANSMISSION COVER SHEET

**Date:** December 2, 2004  
**To:** Monica Young  
**Fax:** 703-746-6617  
**Re:** Patent Application 10/649,391  
**From:** Mindy

**Note:** Ms. Young-  
Pursuant to our phone conversation of today, please find attached Page 8 of the Cement Slab Leveling Apparatus, Patent Application No. 10/649,391 as you requested. As we discussed, our office filed this patent application on August 26, 2003 and have not yet received the Filing Receipt. I understand that Page 8 was incorrectly scanned and some of the wording was missing and that this was the reason for the long delay in processing the filing receipt. Further, I understand that you will process the filing receipt today. If you are in need of anything further, please do not hesitate to contact me.

Thank you for your prompt attention to this matter.

Mindy

**YOU SHOULD RECEIVE 2 PAGE(S), INCLUDING THIS COVER SHEET. IF YOU DO NOT RECEIVE ALL THE PAGES, PLEASE CALL (701) 298-3001.**

THE INFORMATION CONTAINED IN THIS FACSIMILE MESSAGE IS INTENDED ONLY FOR THE PERSONAL AND CONFIDENTIAL USE OF THE DESIGNATED RECIPIENT OR ENTITY NAMED ABOVE. THIS MESSAGE MAY BE AN ATTORNEY-CLIENT COMMUNICATION, AND AS SUCH IS PRIVILEGED AND CONFIDENTIAL. IF THE READER OF THIS MESSAGE IS NOT THE INTENDED RECIPIENT OR AN AGENT RESPONSIBLE FOR DELIVERING IT TO THE INTENDED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT YOU HAVE RECEIVED THIS DOCUMENT IN ERROR, AND THAT ANY REVIEW, DISSEMINATION, DISTRIBUTION OR COPYING OF THIS MESSAGE IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS COMMUNICATION IN ERROR, PLEASE NOTIFY US IMMEDIATELY BY TELEPHONE AND RETURN THE ORIGINAL MESSAGE TO US VIA THE U.S. POSTAL SERVICE. THANK YOU



hydraulic type cylinders that are tied together through the use of a pump cap attached to the upper ends of the cylinder's rams. One of these cylinders is hydraulically activated and operated by the hydraulic system as previously described. Thus, as the  
5 primary cylinder is expanded through the activation of the hydraulic manifold controls, the ram is forced upwards thereby pushing the pump rod cap upwards. By virtue of the cap's tie to the plurality of operational cylinder rams, the operational cylinders are also expanded.

10 The expansion of the operational cylinders draws the fill from the material bin into their interiors through the pump manifold. The pump manifold ties the pump to the bin and is equipped with two one-way valves which control the flow of the fill within the invention. The first of these valves, the  
15 forward one-way valve, lies between the interior of the bin and the pump manifold and functions to allow the flow of fill into the manifold as the cylinders are expanded. Conversely, in this operation the rearward one-way valve lies between the pump manifold and its outlet the manifold pipe and functions to keep  
20 fill in the manifold pipe from being drawn back into the pump manifold.

Once the expansion of the hydraulic cylinder is complete and the operational cylinders are full, the hydraulic cylinder is then contracted which forces the fill within the operational